

526 Rec'd PCT/PTC 29 SEP 2000

FORM PTO-1390
(REV 12-29-99)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

09/647300

INTERNATIONAL APPLICATION NO.

PCT/IB 00/00189

INTERNATIONAL FILING DATE

22 FEBRUARY 2000 (22.02.2000)

PRIORITY DATE CLAIMED

25 FEBRUARY 1999 (25.02.1999)

TITLE OF INVENTION *SPEECH RECOGNITION AND SIGNAL ANALYSIS BY STRAIGHT
SEARCH OF SUBSEQUENCES WITH MAXIMAL CONFIDENCE MEASURE*

APPLICANT(S) FOR DO/EO/US

SILAGHI, MARIUS, CALIN

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☐ This express request to begin national examination procedures (35 U.S.C. 371(f) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C.371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☐ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☒ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19(35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A FIRST preliminary amendment.
☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

*- declaration about the translation of the priority document
- declaration concerning the Information Disclosure Statement*

529 Rec'd PCT/PTC '29 SEP 2000

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)		INTERNATIONAL APPLICATION NO.		ATTORNEY'S DOCKET NUMBER	
09/647300					
17. <input checked="" type="checkbox"/> The following fees are submitted: BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) : Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO \$970.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO. \$840.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$690.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$670.00 International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(1)-(4) \$96.00 ENTER APPROPRIATE BASIC FEE AMOUNT =				CALCULATIONS PTO USE ONLY 	
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	4 - 20 =		X \$18.00	\$	
Independent claims	1 - 3 =		X \$78.00	\$	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00	\$	
TOTAL OF ABOVE CALCULATIONS =				\$ 970	
Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				\$ 485	
SUBTOTAL =				\$ 485	
Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$	
TOTAL NATIONAL FEE =				\$ 485	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property				+ \$ 0	
TOTAL FEES ENCLOSED =				\$ 485	
				Amount to be refunded:	\$
				charged:	\$

- a. ☐ A check in the amount of \$_____ to cover the above fees is enclosed.
- b. ☐ Please charge my Deposit Account No. _____ in the amount of \$_____ to cover the above fees.
A duplicate copy of this sheet is enclosed.
- c. ☐ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. _____. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO.

OCT-2 2003

RECEIVED

SILAGHI, ANNE, MELODY
RUE DE LA BLANCHERIE 13
CH-1022 CHAVANNE PRES-REMENS
SWITZERLAND

SIGNATURE

SILAGHI, MARINUS, CALIN
NAME

REGISTRATION NUMBER

Speech Recognition and Signal Analysis by straight Search of Subsequences with Maximal Confidence Measure

1 Field of the invention

The invention relates to a common component of:

- Speech Recognition
- Keyword Spotting
- Segments Alignment for DNA and proteins (Human Genome)
- Recognition of Objects in Images

2 Background Art

This invention addresses the problem of *keyword spotting (KWS)* in unconstrained speech without explicit modeling of non-keyword segments (typically done by using filler HMM models or an ergodic HMM composed of context dependent or independent phone models without lexical constraints). Although several algorithms (sometimes referred to as “sliding model methods”) tackling this type of problem have already been proposed in the past, e.g., by using Dynamic Time Warping (DTW) [4] or Viterbi matching [9] allowing relaxation of the (begin and endpoint) constraints, these are known to require the use of an “appropriate” normalization of the matching scores since segments of different lengths have then to be compared. However, given this normalization and the relaxation of begin/endpoints, straightforward Dynamic Programming (DP) is no longer optimal (or, in other words, the DP optimality principle is no longer valid) and has to be adapted, involving more memory and CPU. Indeed, at any possible ending time e , the match score of the best warp and start time b of the reference has to be computed [4] (for all possible start times b associated with unpruned paths). Moreover, in [9], and in the same spirit than what is presented here, for all possible ending times e , the average observation likelihood along the most likely state

sequence is used as scoring criterion. Finally, this adapted DP quickly becomes even more complex (or intractable) for more advanced scoring criteria (such as the confidence measures mentioned below).

More recently, work in the field of confidence level, and in the framework of hybrid HMM/ANN systems, it was shown [1] that the use of accumulated local posterior probabilities (as obtained at the output of a multilayer perceptron) normalized by the length of the word segment (or, better, involving a double normalization over the number of phones and the number of acoustic frames in each phone) was yielding good confidence measures and good scores for the re-estimation of N -best hypotheses. Similar work, where this kind of confidence measure was compared to several alternative approaches, was reported in [8] and confirmed this conclusion. However, so far, the evaluation of such confidence measures involved the estimation and rescoring of N -best hypotheses. Similar work and conclusions (also using N -best rescoring) were also reported in using likelihood ratio rescoring and non-keyword rejection [7].

2.1 KWS without filler models

Let $X = \{x_1, x_2, \dots, x_n, \dots, x_N\}$ denote the sequence of acoustic vectors in which we want to detect a keyword, and let M be the HMM model of a keyword M and consisting of L states $\mathcal{Q} = \{q_1, q_2, \dots, q_\ell, \dots, q_L\}$. Assuming that M is matched to a subsequence $X_b^e = \{x_b, \dots, x_e\}$ ($1 \leq b \leq e \leq N$) of X , and that we have an implicit (not modeled) *garbage/filler state* q_G preceding and following M , we define (approximate) the log posterior of a model M given a subsequence X_b^e as the average posterior probability along the optimal path, i.e.:

$$\begin{aligned} -\log P(M|X_b^e) &\simeq \frac{1}{e-b+1} \min_{Q \in \mathcal{M}} -\log P(Q|X_b^e) \\ &\simeq \frac{1}{e-b+1} \min_{Q \in \mathcal{M}} \{-\log P(q^b|q_G) \\ &\quad - \sum_{n=b}^{e-1} [\log P(q^n|x_n) + \log P(q^{n+1}|q^n)] \\ &\quad - \log P(q^e|x_e) - \log P(q_G|q^e)\} \end{aligned} \quad (1)$$

where $Q = \{q^b, q^{b+1}, \dots, q^e\}$ represents one of the possible paths of length $(e-b+1)$ in M , and q^n the HMM state visited at time n along Q , with $q^n \in \mathcal{Q}$. In this expression, q_G represents the “garbage” (filler) state which is simply used here as the non-emitting initial and final state of M . Transition probabilities $P(q^b|q_G)$ and $P(q_G|q^e)$ can be interpreted as the keyword

entrance and exit penalties, as optimized in [3], but these have not been optimized here. In our case, local posteriors $P(q_\ell|x_n)$ were estimated as output values of a multilayer perceptron (MLP) used in a hybrid HMM/ANN system [2].

For a specific sub-sequence X_b^e , expression (1) can easily be estimated by dynamic programming since the sub-sequence and the associated normalizing factor $(e - b + 1)$ are given. However, in the case of keyword spotting, this expression should be estimated for all possible begin/endpoint pairs $\{b, e\}$ (as well as for all possible word models), and we define the matching score of X on M as:

$$S(M|X) = -\log P(M|X_{b^*}^{e^*}) \quad (2)$$

where the optimal begin/endpoints $\{b^*, e^*\}$, and the associated optimal path Q^* , are the ones yielding the lowest average local posterior:

$$\langle Q^*, b^*, e^* \rangle = \operatorname{argmin}_{\{Q, b, e\}} \frac{-1}{e - b + 1} \log P(Q|X_b^e) \quad (3)$$

Of course, in the case of several keywords, all possible models will have to be evaluated.

As shown in [1, 8], a double averaging involving the number of frames per phone and the number of phones will usually yield slightly better performance:

$$\langle Q^*, b^*, e^* \rangle = \operatorname{argmin}_{\{Q, b, e\}} \frac{-1}{J} \sum_{j=1}^J \left(\frac{1}{e_j - b_j + 1} \sum_{n=b_j}^{e_j} \log P(q_j^n|x_n) \right) \quad (4)$$

where J represents the number of phones in the hypothesized keyword model and q_j^n the hypothesized phone q_j for input frame x_n .

However, given the time normalization and the relaxation of begin/endpoints, straightforward DP is no longer optimal and has to be adapted, usually involving more memory and CPU. A new (and simple) solution to this problem is proposed in Section 3.1.

2.2 Filler-based KWS

Although various solutions have been proposed towards the direct optimization of (2) as, e.g., in [4, 9], most of the keyword spotting approaches today prefer to preserve the optimality and simplicity of Viterbi DP by modeling the complete input [5] and explicitly [6] or implicitly [3] modeling non-keyword segments by using so called filler or garbage models as additional reference models. In this case, we assume that non-keyword segments are modeled

by extraneous garbage models/states q_G (and grammatical constraints ruling the possible keyword/non-keyword sequences).

Let us consider only the case of detecting one keyword per utterance at a time. In this case, the keyword spotting problem amounts at matching the whole sequence X of length N onto an extended HMM model \overline{M} consisting of the states $\{q_G, q_1, \dots, q_L, q_G\}$, in which a path (of length N) is denoted $\overline{Q} = \{\overbrace{q_G, \dots, q_G}^{b-1}, q^b, q^{b+1}, \dots, q^e, \overbrace{q_G, \dots, q_G}^{N-e}\}$ with $(b-1)$ garbage states q_G preceding q^b and $(N-e)$ states q_G following q^e , and respectively emitting the vector sequences X_1^{b-1} and X_{e+1}^N associated with the non-keyword segments.

Given some estimation of $P(q_G|x_n)$ (e.g., using probability density functions trained on non keyword utterances), the optimal path \overline{Q}^* (and, consequently b^* and e^*) is then given by:

$$\begin{aligned} \overline{Q}^* &= \underset{\forall \overline{Q} \in \overline{M}}{\operatorname{argmin}} -\log P(\overline{Q}|X) \\ &= \underset{\forall \overline{Q} \in \overline{M}}{\operatorname{argmin}} \{-\log P(Q|X_b^e) \\ &\quad - \sum_{n=1}^{b-1} \log P(q_G|x_n) - \sum_{n=e+1}^N \log P(q_G|x_n)\} \end{aligned} \quad (5)$$

which can be solved by straightforward DP (since all paths have the same length). The main problem of filler-based keyword spotting approaches is then to find ways to best estimate $P(q_G|x_n)$ in order to minimize the error introduced by the approximations. In [3], this value was defined as the average of the N best local scores while, in other approaches, this value is generated from explicit filler HMMs. However, these approaches will usually not lead to the “optimal” solution given by (2).

3 Disclosure of Invention

3.1 Iterating Viterbi Decoding (IVD)

In the following, we show that it is possible to define an iterative process, referred to as *Iterating Viterbi Decoding (IVD)* with good/fast convergence properties, estimating the value of $P(q_G|x_n)$ such that straightforward DP (5) yields exactly the same segmentation (and recognition results) than (3). While the same result could be achieved through a modified DP in which all possible combinations (all possible begin/endpoints) would be taken into account, it is possible to show that the algorithm proposed below is more efficient (in terms

of both CPU and memory requirements).

Here, I will use a similar scoring technique for keyword spotting without explicit filler model. Compared to previously devised “sliding model” methods (such as [4, 9]), the first algorithm proposed here is based on:

1. A matching score defined as the average observation posterior along the most likely state sequence. It is indeed believed that local posteriors (or likelihood ratios, as in [7]) are more appropriate to the task.
2. The iteration of a Viterbi decoding algorithm, which does not require scoring for all begin/endpoints or N-best rescoring, and which can be proved to (quickly) converge to the “optimal” (from the point of view of the chosen scoring functions) solution without requiring any specific filler models, using straightforward Viterbi alignments (similar to regular filler-based KWS, but at the cost of a few iterations).

3.2 IVD: Description

The IVD algorithm is based on the same criterion than the filler based approaches (5), but rather than looking for explicit (and empirical) estimates of $P(q_G|x_n)$ we aim at mathematically estimating its value (which will be different and adapted to each utterance) such that solving (5) is equivalent to solving (3). Thus, we perform an iterative estimation of $P(q_G|x_n)$, such that the segmentation resulting of (5) is the same than what would be obtained from (3).

Defining $\varepsilon = -\log P(q_G|x_n)$, the proposed algorithm can be summarized as follows:

1. Start from an initial value $\varepsilon_0 = \varepsilon$ (it is actually proven that the iterative process presented here will always converge to the same solution (in more or less cycles, with the worst case upper bound of N iterations) independently of this initialization), (e.g., with ε equal with a cheap estimation of the score of a “match”). In the experiments reported below, ε was initialized to $-\log$ of the maximum of the local probabilities $P(q_k|x_n)$ for each frame x_n .

An alternative choice could be to initialize ε_0 to a pre-defined score that expression (1) should reach to declare a keyword “matching” (see point 4 below). In this last case, if ε increases at the first iteration, then we can (as proven) directly infer that the match will be rejected, otherwise it will be accepted.

2. Given the current estimate ε_t of $P(q_G|x_n)$ at iteration t , find the optimal path $\langle \bar{Q}_t, b_t, e_t \rangle$ according to (5) and matching the complete input.
3. Update ($t = t+1$) the estimated value of ε_t , defined as the average of the local posteriors along the optimal path Q_t (matching the $X_{b_t}^{e_t}$ resulting of (5) on the keyword model) i.e.:

$$\varepsilon_{t+1} = -\frac{1}{(e_t - b_t + 1)} \log P(Q_t | X_{b_t}^{e_t}) \quad (6)$$

4. Return to (2) and iterate until convergence. If we are not interested in the optimal segmentation, this process could also be stopped as soon as ε reaches a (pre-defined) minimum threshold below which we can declare that a keyword has been detected.

Correctness and convergence proof of this process and generalization to other criteria, are available: each IVD iteration (from the second iteration) will decrease the value of ε_t , and the final path yields the same solution than (3).

3.3 One-pass keyword spotting

3.3.1 General Description

The above algorithm has a very good experimental convergence speed (3-5 iterations in our tests). However, the worst case theoretical convergence speed of the process is N . For this reason, a one step computation is potentially interesting. In the next subsection we show that the standard DP cannot be used for solving the equation (3).

3.3.2 The Principle of Optimality

Let us define $T(\bar{M}, X)$ as the DP table of emission probabilities for an utterance X and the states of the hypothesized word W . When solving by standard DP, we would compute for each entry of the table $T(\bar{M}, X)$ at frame k of X and state s of \bar{M} three values: S_{ks} , L_{ks} and C_{ks} , where S_{ks} corresponds to the sum of the posteriors on the optimal path that leads to the entry, L_{ks} holds the length of the optimal path computed so far, and C_{ks} is the estimation of the cost on the optimal expanded path.

By a path leading to an entry $T(k, s)$ we mean a sequence of entries in the table T , such that there is exactly an entry for each time frame $t \leq k$. At each entry $T(k, s)$, DP selects a locally optimal path noted P_{ks} .

At each step k , we consider all pairs of entries of table $T(\overline{M}, X)$ of type $T(k, s), T(k-1, t)$. We update for each such pair, the current cost C_{ks} (initially ∞), by comparing it with the alternative given by:

$$\begin{aligned} S_{ks} &= S_{(k-1)t} - \log p(s|x_k)p(s|t) \\ L_{ks} &= L_{(k-1)t} + 1, \forall t > 0, t \leq L \\ C_{ks} &= \frac{S_k}{L_k} \end{aligned} \quad (7)$$

wanting to have at step k the path P_{ks} from the paths $P_{(k-1)t}$ that minimizes C_{NL} . With DP, one will choose the P_{ks} with minimal C_{ks} .

In order for the previous computation to be correct, the optimality principle needs to be respected. The optimality principle of Dynamic Programming requires that the path to the frame $k-1$ that minimizes C_{NL} , also minimizes C_{ks} for an entry at frame k of table $T(\overline{M}, X)$. We have proved that the expression 7 does not respect the optimality principle of Dynamic Programming

3.3.3 Pruning with beam search

The Dynamic Programming can be viewed as a set of safe prunings that are applied at each entry of the DP table and has the property that only one alternative is maintained. We have thus shown that Dynamic Programming cannot be used, since the principle of optimality is not respected. We try therefore to detect the type of safe pruning that can be done.

We have proved that if at a frame a we have two paths P'_a and P''_a with $S''_a < S'_a$ and $L'_a < L''_a$, then at no frame $c \geq a$ will a path P''_c be forsaken for a path P'_c if $P'_a \subset P'_c$, $P''_a \subset P''_c$ and $P'_c \setminus P'_a \equiv P''_c \setminus P''_a$. We will note the order relation as $P''_a \prec P'_a$. We have further shown that a path P' may be discarded only for a lower cost one, P'' .

$$P' \prec P'' \Rightarrow C'_k < C''_k \quad (8)$$

Thus, algorithm 1 computes $S(M, X)$ and Q^* from equation (3).

By ordering the set of paths, according to Equation 8, we only need to check the line 1.2 of algorithm 1 up to the eventual insertion place. The last paths are candidates for pruning in line 1.1. In order for the pruning to be acceptable, we will prune only paths that were too long on the last state. An additional counter is needed for storing the state length. This counter is reset when the state is changed and is incremented at each advance with a frame.

```

procedure OneStep(W,X)
  SetOfPaths(1..N, 1..K) ← ∅
  for all frame=1; frame ≤ N; frame++ do
    for all state=1; state ≤ K; state++ do
      for all candidate  $p_i \in \text{SetOfPaths}(\text{frame}-1, 1..K)$  do
        Add( $p_i$ , SetOfPaths[frame, state])
      end
    end
  end
  SetOfPaths[frame, K] ← best of the candidates
end.

procedure Add(path, set-of-paths)
  for all  $p_i \in \text{set-of-paths}$  do
    1.1 if path <  $p_i$  then
      | delete  $p_i$ 
    end
    1.2 if  $p_i$  < path then
      | return
    end
  end
  Insert  $p_i$  in set-of-paths
end.

```

Algorithm 1: One Step Algorithm

3.4 One pass confidence-based keyword spotting

3.4.1 The Method of Double Normalization

The corresponding confidence measure is defined as:

$$\frac{1}{NVP} \sum_{p_i \in VP} \frac{\sum_{pst \in p_i} -\log(pst)}{\text{length}(p_i)} \quad (9)$$

where NVP stands for the *number of visited phonemes* and VP stands for the *set of visited phonemes*. An average is computed over all posteriors *pst* of the emission probabilities for the time frames matched to the visited phoneme p_i . The function *length*(p_i) gives the number of time frames matched against p_i .

This method consists into a breath first Beam Search algorithm. It refers to a set of

reduction rules and certain normalizations:

For the state q_G , in this method, the logarithm of the emission posterior is equal with zero. For each frame e and for each state s , the set of paths/probabilities of having the frame e in the state s is computed as the first N maxima (N can be finite) of the confidence measure for all paths in HMM \overline{M} of length e and ending in the state s . The paths that according to the reduction rules will loose the final race when compared with another already known path, will be deleted as well.

We note a_1, p_1, l_1, a_2, p_2 and l_2 the confidence measure for the previous phonemes, the posterior in the current phoneme and the length in the current phoneme for the path Q_1 , respectively the path Q_2 . The rules that may be used for the reduction of the search space by discarding a path Q_1 for a path Q_2 are in this case any of the next ones:

1. $l_2 \geq l_1, A > 0, B \leq 0$ and $L_c^2 A + L_c B + C \geq 0$
2. $l_2 \geq l_1, A \geq 0, B \geq 0$ and $C \geq 0$
3. $l_2 \geq l_1, A \leq 0, C \geq 0$ and $L^2 A + LB + C \geq 0$
4. $l_2 \geq l_1, A = 0, B < 0$ and $LB + C \geq 0$

where $A = a_1 - a_2, B = (a_1 - a_2)(l_1 + l_2) + p_1 - p_2, C = (a_1 - a_2)l_1 l_2 + p_1 l_2 - p_2 l_1, L = L_{max} - \max\{l_1, l_2\}, L_c = -B/2A \geq 0$ and L_{max} is the maximum acceptable length for a phoneme.

By discarding paths only if one of the above rules is satisfied, the optimum defined by the confidence measure with double normalization can be guaranteed, if no phone may be avoided by the HMM M . Any HMM may be decomposed in HMMs with this quality. The 4-th rule is included in the 3-rd and its test is useless if the last one was already checked.

First test, $l_2 \geq l_1$ tells us if Q_2 has chances to eliminate Q_1 , otherwise we will check if Q_1 eliminates Q_2 . These tests were inferred from the conditions of maintaining the final maximal confidence measure while reduction takes place. In order to use the method of double normalization without decomposing HMMs that skip some phonemes, the previous rules are modified taking into account the number of visited phonemes for any path F_1 respectively F_2 and the number of phonemes that may follow the current state.

A simplified test may be:

- $l_2 \geq l_1, A \geq 0, p_1 \geq p_2$ respectively $F_2 \geq F_1$ for the HMMs that skips phonemes.

This test is weaker than the 2nd reduction rule. For example a path is eliminated by a second path if the first one has an inferior confidence measure (higher in value) for the the previous phonemes, a shorter length and the minus of the logarithm of the cumulated posterior in the current phoneme also inferior (higher in value) to that of the second one.

An additional confidence measure based on the maximal length, L_{max} , and on the maximum of the minus of the logarithm of the cumulated and normalized posterior in phoneme, P_{max} , can be used in order to limit the number of stored paths.

- $p > L_{max}P_{max}$ in any state
- $\frac{p}{l} > P_{max}$ at the output from a phoneme

where p and l are the values in the current phoneme for the minus of the logarithm of cumulated posterior and for the length of the path that is discarded. These tests allow for the elimination of the paths that are too long without being outstanding, respectively of the paths with phonemes having unacceptable scores, otherwise compensated by very good scores in other phonemes.

If N is chosen equal with one, the aforementioned rules are no longer needed, but always we propagate the path with the maximal current estimation of the confidence measure. The obtained results are very good, even if the defined optimum is guaranteed for this method only when N is bigger than the length of the sequence allowed by L_{max} or of the tested sequence.

The same approach is valid for the simple normalization, where the HMM for the searched word will be grouped into a single phoneme.

3.4.2 The Method of Real Fitting

We have also defined a new confidence measured that represents differently the exigencies of the recognition. Since the phonemes and the absent states can be modeled by the used HMMs, we find it interesting to request the fitting of each phoneme in the model with a section of the sequence. Therefore, we measure the confidence level of a subsequence as being equal with the maximum over all phonemes of the minus of the logarithm of the cumulated posterior of the phone, normalized with its length.

$$\max_{\text{phonem} \in \text{Visited Phonems}} \frac{\sum_{\text{phonem}} -\log(\text{posteriors})}{\text{phonem length}} \quad (10)$$

The rule that may be used in this framework for the reduction of the number of visited paths is:

- Q_2 is discarded in favor of another path Q_1 if the confidence measure of the Real Fitting for the previous phonemes is inferior (higher in value) for Q_2 compared with Q_1 , and if $p_1 \leq p_2$ and $l_2 \leq l_1$.

where p_1, l_1, p_2, l_2 represent the minus of the logarithm of the cumulated posterior respectively the number of frames in the current phoneme for the path Q_1 respectively Q_2 .

Similarly to the previous method, the set of visited paths can be pruned by discarding those that:

- $p > L_{max}P_{max}$ in any state
- $\frac{p}{l} > P_{max}$ at the output from a phoneme

where p and l are the values in the current phoneme for the minus of the logarithm of the cumulated posterior and for the length of the path that is discarded. We recall that the meaning of the constants are the maximal length L_{max} , respectively the accepted maxima of the minus of the logarithm of the cumulated and normalized posterior in phoneme, P_{max} .

3.5 Conclusions

We have thus proposed a new method for keyword spotting, based on recent advances in confidence measures, using local posterior probabilities, but without requiring the explicit use of filler models.

A new algorithm, referred to as *Iterating Viterbi Decoding (IVD)*, to solve the above optimization problem with a simple DP process (not requiring to store pointers and scores for all possible ending and start times), at the cost of a few iterations. Other three beam-search algorithms corresponding to three different confidence measures were also described.

While the proposed approach allows for an easy generalization to more complex criteria, preliminary results obtained on the basis of 100 keywords (and without any specific tuning) appear to be particularly competitive to other alternative approaches.

3.6 The object of the invention consists of:

- Method of recognition of a subsequence using a direct maximization of confidence measures.

- The method of IVD for directly maximizing the confidence measures based on simple normalization.
- The use of the confidence measure and method of recognition named 'Real Fitting', based on individual fitting for each phoneme.
- Methods of recognition using simple and double normalization by:
 - combining these measures with additional confidence measures mentioned here, respectively the maximal length and real matching limitation.
- The use of the aforementioned methods in keyword recognition.
- The use of the aforementioned methods in subsequence recognition of organic matter.
- The use of the aforementioned methods in recognition of objects in images.

4 Best Mode for Carrying Out the Invention

Execution: It is necessary to use a computer, but the method can also be implemented in hardware.

1. A representation under the form of an HMM is obtained for the subsequences that are looked for (word, protein profile, section of an image of the object).
2. A tool will be obtained (eventually trained Ex: for speech recognition) for the estimation of the posteriors. For example multi-Gaussians, neuronal networks, clusters, database with Generalized Profiles and mutation matrices (PAM, BLOSSUM, etc.).
3. One of the proposed algorithms should be implemented. They yield close performance but the method of Real Fitting coupled with a well checked dictionary should perform best.

For the first algorithm (IVD)

- (a) The classic algorithm of Viterbi is implemented with the modification that, for each pair $P = \langle \text{sample}, \text{state} \rangle$ one propagates the moments of transition between the state q_G and the states of the HMM M for the path that arrives at P. These are inherited from the path that wins the entrance in the pair P, excepting for

the moment when their decision is taken, namely when they receive the index of the corresponding sample.

- (b) $w = -\log P(M|X_b^e)$ is computed by subtracting from the cumulated posterior that is returned by the Viterbi algorithm for the path Q_b^e , the value $(N - (e - b + 1)) * \varepsilon$ corresponding to the contribution of the states q_G and dividing the result through $e - b + 1$. $e - b + 1$ from the previous formula can be factorized outside the fraction.
- (c) The initialization of ε is made with an expected mean value. One can use the w that is computed when the state q_G is associated with an emission posterior equal to the average of the best K emission probabilities of the current sample as done in the well-known "garbage on-line model". In this case, K is trained using the corresponding technique.

The next 'Beam search' algorithms, are implemented according to the description in the corresponding sections. For each pair $P = \langle sample, state \rangle$ one computes for each corresponding path the sum and length in the last phoneme, as well as the sum over the normalized cumulated posteriors of the previous phonemes (and their number). Also, the entrance and exit samples into the HMM M are computed and propagated like in the previous method, in order to ensure the localization of the subsequence.

4. If one searched entity (keyword, sequence, object) can have several HMM models, all of them are taken into consideration as competitors. This is the case of the words with several pronunciations (or of the objects that have different structures in different states, for the recognition in images).

After the computation of the confidence measure for each model of the subsequences, one eliminates those with a confidence measure in disagreement with a 'threshold' that is trained for the configuration and the goal of the given application. For example, for speech recognition with neuronal networks and minus of the logarithm of the posteriors, the 'threshold' is chosen in the wanted point of the ROC curve obtained in tests.

5. The remained alternatives are extracted in the order of their confidence measure and with the elimination of the conflicting alternatives until exhaustion. Each time when an alternative is eliminated, the searched entity with the corresponding HMM is re-estimated for the remaining sections in the sequence in which the search is performed.

If the new confidence measure passes the test of the 'threshold', then it will be inserted in the position corresponding to its score in the queue of alternatives.

6. The successful alternatives can undergo tests of superior levels like for example a question of confirmation for speech recognition, opinion of one operator, etc.
7. For objects recognition in images:

Posteriors are obtained by computing a distance between the color of the model and that of element in the section of the image. If the context requires, the image will be preprocessed to ensure a certain normalization (Ex: changeable conditions of light will make necessary a transformation based on the histogram).

The phonemes of the speech recognition correspond to parts of the object. The structure (existence of transitions and their probabilities) can be modified, function of the characteristics detected along the current path. For example, after detecting regions of the object with certain lengths, one can estimate the expected length of the remaining regions. Thus, the number of the expected samples for the future states can be established and the HMM attached to the object will be configured accordingly.

A direction is scanned for the detection of the best fitting and afterwards, other directions will be scanned for discovering new fittings, as well as for testing the previous ones. The final test will be certified by classical methods such as cross-correlation or by the analysis of the contours in the hypothesized position.

5 Industrial Applicability

Here we present some examples for the application of the proposed method in the industry:

- The recognition of keywords begins to be used in answering automates of banking system as well as telephone and automates for control, sales or information. The method offers a possibility to recognize keywords in spontaneous speech with multiple speakers.
- The recognition of DNA sequences is important for the study of the human Genome. One of the biggest problem of the involved techniques consists in the high quantity of data that have to be processed.

- The recognition of objects in images is used, among others, in cartography and in the coordination of industrial robots. The method allows a quick estimation of the position of the objects in scenes and can be validated with extra tests, using classical methods of cross-correlation.

References

- [1] Bernardis, G. and Boulard, H., "Improving posterior-based confidence measures in hybrid HMM/ANN speech recognition systems," *Proceedings of Intl. Conf. on Spoken Language Processing* (Sydney, Australia), pp. 775-778, 1998.
- [2] Boulard, H. and Morgan, N., *Connectionist Speech Recognition - A Hybrid Approach*, Kluwer Academic Publishers, 1994.
- [3] Boulard, H., D'Hoore, B., and Boite, J.-M., "Optimizing recognition and rejection performance in wordspotting systems," *Proc. of IEEE Intl. Conf. on Acoustics, Speech, and Signal Processing* (Adelaide, Australia), pp. I:373-376, 1994.
- [4] Bridle, J.S., "An efficient elastic-template method for detecting given words in running speech," *Proc. of the Brit. Acoust. Soc. Meeting*, pp. 1-4, April 1973.
- [5] Rohlicek, J.R., "Word spotting," in *Modern Methods of Speech Processing*, R.P. Ramachandran and R. Mammone (Eds.), Kluwer Academics Publishers, pp. 123-157, 1995.
- [6] Rose, R.C. and Paul, D.B., "A hidden Markov model based keyword recognition system," *Proc. of ICASSP'90*, pp. 129-132, 1990.
- [7] Sukkar, R.A. and Lee, C.-H., "Vocabulary independent discriminative utterance verification for nonkeyword rejection in subword based speech recognition," *IEEE Trans. on Speech and Audio Processing*, vol. 4, no. 6, pp. 420-429, 1996.
- [8] Williams, G. and Renals, S., "Confidence measures for hybrid HMM/ANN speech recognition," *Proceedings of Eurospeech'97*, pp. 1955-1958, 1997.
- [9] Wilpon, J.G., Rabiner, L.R., Lee C.-H., and Goldman, E.R., "Application of hidden Markov models of keywords in unconstrained speech," *Proc. of ICASSP'89*, pp. 254-257, 1989.

Independent Claim 1.

Preamble:

Recognizes subsequences, represented as Hidden Markov Models (HMM), that are searched for in a given sequence.

We refer to the confidence measures, that are used for the reclassification of the winning hypotheses in Speech Recognition. These are some examples of such measures:

simple normalization = accumulated posterior, normalized
with the length of the subsequence

double normalization = double normalization of the accumu-
lated posterior over the number of
phonemes and over the number of
acoustic samples in each phoneme.

characterized by: It allows the additional confidence measure, based on the extremes of the values of the logarithm of the accumulated posterior in each phoneme, normalized with its length. We call this measure 'real fitting'.

$$\max_{\text{phoneme} \in \text{Visited Phonemes}} \frac{\sum_{\text{phoneme}} -\log(\text{posteriors})}{\text{phoneme length}}$$

characterized by: It searches the subsequences that offer the maximization of one mentioned confidence measures, over all possible matchings.

characterized by: It allows the revaluation of the alternatives that offer the highest among any mentioned confidence measure on the basis of another confidence measure.

characterized by: It computes the alternative that maximizes the 'simple normalization' by using the method that we have called 'Iterative Viterbi Decoding' and that estimates

the emission probability of the filler states, in an iterative manner, as being equal to the confidence measure in the previous iteration.

characterized by: It computes the alternative that maximizes the 'simple normalization', 'double normalization' or 'real fitting' using an algorithm that considers the emission probability of the filler state as zero. This method computes progressively, for each pair of sample and state of HMM, a set of possible alternatives paths to reach it. The computation of this set is based on the sets of paths that lead to the states that can be associated to the previous sample.

This set can be reduced by using the given appropriate rules for the given confidence measure, ensuring the correctness of the inference.

This set can be also reduced by using heuristics that are based on the aforementioned rules, for speeding up the computation despite the risk of reducing the theoretical quality of the recognition.

Dependent Claim 2.

Preamble:

It is based on the Claim 1.

It estimates the existence of keywords and their position in utterances.

characterized by: It uses the methods described in Claim 1, for recognition of subsequences represented by Hidden Markov Models.

Dependent Claim 3.

Preamble:

It is based on the Claim 1.

It estimates the existence of biomolecular subsequences and their position in the chains of DNA using models like generalized profiles.

characterized by: The estimation of their existence and position is made according to the methods described in the Claim 1, for recognition of subsequences represented by Hidden Markov Models.

Dependent Claim 4.

Preamble:

It is based on the Claim 1. It carries out the estimation of the existence of objects and their position in images.

characterized by: It uses the methods described in Claim 1, for the recognition of subsequences represented by Hidden Markov Models (HMM).

characterized by: Sections through views of virtual objects are modeled by sets of Hidden Markov Models.

characterized by: It uses a probabilistic model based on a distance computed between colors.

characterized by: The Hidden Markov Models that model the objects can be structured of distinct regions, that play in the frame of the method the role of the phonemes.

characterized by: The models of the objects can be modified in a dynamic manner with respect to the transition properties (existence and probability) on the basis of the accumulated information during the fitting process.

**STATEMENT CLAIMING SMALL ENTITY STATUS
(37 CFR 1.9(f) & 1.27(b))--INDEPENDENT INVENTOR**

Docket Number (Optional)

Applicant, Patentee, or Identifier: _____

Application or Patent No.: _____

Filed or Issued: _____

Title: SPEECH RECOGNITION AND SIGNAL ANALYSIS BY STRAIGHT SEARCH
OF SUBSEQUENCES WITH MAXIMAL CONFIDENCE MEASURE

As a below named inventor, I hereby state that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees to the Patent and Trademark Office described in:

- ☒ the specification filed herewith with title as listed above.
☐ the application identified above.
☐ the patent identified above.

I have not assigned, granted, conveyed, or licensed, and am under no obligation under contract or law to assign, grant, convey, or license, any rights in the invention to any person who would not qualify as an independent inventor under 37 CFR 1.9(c) if that person had made the invention, or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern, or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below:

- ☒ No such person, concern, or organization exists.
☐ Each such person, concern, or organization is listed below.

Separate statements are required from each named person, concern, or organization having rights to the invention stating their status as small entities. (37 CFR 1.27)

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

SILAGHI, MARIUS, CALIN

NAME OF INVENTOR

NAME OF INVENTOR

NAME OF INVENTOR

[Signature]

Signature of inventor

Signature of inventor

Signature of inventor

12.05.00

Date

Date

Date

Vu pour légalisation de la signature
apposée ci-dessus ci-dessous
par Monsieur Marius Colin Silaghi
Lausanne, le douze septembre deux mille
Emolument Fr. 12.- No 1926
Le juge de paix: *[Signature]*



Please type a plus sign (+) inside this box → ☒

PTO/SB/01 (12-97)
Approved for use through 9/30/00. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

U.S. Parent Application or PCT Parent Number	Parent Filing Date (MM/DD/YYYY)	Parent Patent Number (if applicable)

☐ Additional U.S. or PCT international application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto.

As a named inventor, I hereby appoint the following registered practitioner(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

☐ Customer Number

OR

☐ Registered practitioner(s) name/registration number listed below

Place Customer
Number Bar Code
Label here

Name	Registration Number	Name	Registration Number

☐ Additional registered practitioner(s) named on supplemental Registered Practitioner Information sheet PTO/SB/02C attached hereto.

Direct all correspondence to: ☐ Customer Number or Bar Code Label

OR ☒ Correspondence address below

Name	SILAGHI, ANNE, MELODY				
Address	RUE DE LA BLANCHERIE 13				
Address					
City	CHAVANNE PRES RENENS	State	VD	ZIP	CH-1022
Country	SWITZERLAND	Telephone	+41-21-6353358	Fax	+41-21-9433777

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name of Sole or First Inventor:

☐ A petition has been filed for this unsigned inventor

Given Name (first and middle (if any))		Family Name or Surname					
MARIUS CALIN		SILAGHI					
Inventor's Signature			Date	12.09.00			
Residence: City	BAIL MARE	State		Country	ROMANIA	Citizenship	RO
Post Office Address							
Post Office Address							
City		State		ZIP		Country	

☐ Additional inventors are being named on the _____ supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

(Convention de La Haye du 5 octobre 1961)

Le présent acte public

3. agissant en qualité de juge de paix

Attesté

5. à Lausanne 6. le 12 septembre 2000

7. par la Chancellerie d'Etat du Canton de Vaud

8. sous No 6927

29 Niveau/timbre:

10. Signature
pr le Chancelier d'Etat:

Enrollment: Fr. 25,--

L. Volckeva

